



EZY-PAK™ #115

PACKING FOR USE IN EXPANDING TYPE GATE VALVES

DESCRIPTION

EZY-PAK™ #115, the most used packing compound, is designed specifically for use in expanding gate type valve stem glands. Formulated from synthetic fluid and fibers plus inert fillers and a high percentage of ground PTFE particles for performance over a wide temperature range **EZY-PAK #115** is ideal for preventing leaks while lowering the torque required to operate the valve.

EZY-PAK #115 can be pumped using a high-pressure lubricator, or may be formed by hand into any void requiring a packing compound. Excellent for use with hydrocarbons, aqueous solutions, brine, dilute acids, dilute alkalis, water and steam.

- Nontoxic
- Color: Green
- Water Resistant
- Seals
- Asbestos Free
- Nonhazardous
- Contains PTFE
- Pumpable
- Lubricates
- Corrosion Resistant

APPLICATIONS

EZY-PAK #115 is an injectable packing that can be pumped into the stem gland of expanding gate valves through ball check fittings on the body or bonnet **EZY-PAK #115** can also be shaped by hand and pressed into any area requiring leak-free seal or packing.

SERVICE RECOMMENDATIONS

- Crude Oil
- LPG Systems
- Aqueous Solutions
- Steam
- Kerosene
- Liquid & Gas Aliphatic Hydrocarbons
- Propane
- Brine
- Water
- Gasoline
- Natural Gas
- Crude Distillates

TEMPERATURE RANGE

-80°F (-62°C) to 550°F (288°C)

PRODUCT CHARACTERISTICS

Appearance	Green
	Semi-plastic Mass
Penetration (ASTM D-217)	30 – 50
Density (lb/gal) Typical	11.5
Specific Gravity	1.38
Dropping Point (ASTM D-2265)	None
Oil Separation Wt. % (ASTM D-6184)	1.0 max.
Thickener	PTFE, Mineral Silicates and Polymers
Flash Point (ASTM D-92)	> 500°F (260°C)

Note: Not for use with oxygen or strong oxidizers.

For package types and part numbers contact sales@jetlube.com

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.