



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 16-Jul-2018

Revision Date 21-Feb-2019

Revision Number 5



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name JET-LUBE® MARINE MOLY AEROSOL

Other means of identification

Product Code(s) 65041

(M)SDS Number 1363158

Synonyms MARINE MOLY AEROSOL

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube ,LLC.

Address Jet Lube LLC
930 Whitmore Drive
Rockwall, Texas USA 75087

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number 1-888-771-7775

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Specific target organ toxicity (repeated exposure)

Category 1



Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases Under Pressure	Liquefied Gas

Appearance Black**Physical state** Aerosol**Odor** Petroleum**GHS Label elements, including precautionary statements****Danger****Hazard statements**

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture**Synonyms**

MARINE MOLY AEROSOL

Chemical Name	CAS-No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	35 - 40	-	-
Petroleum distillates	68476-85-7	20 - 25	-	-
Residual oils (petroleum), solvent refined	64742-01-4	20 - 25	-	-
Graphite	7782-42-5	5-10	-	-
Molybdenum (IV) sulfide	1317-33-5	<1.0	-	-

4. FIRST AID MEASURES

First aid measures**General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed**Symptoms**

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	Yes.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
-----------------------------	---

Other Information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
--------------------------	--

Environmental precautions

Environmental precautions	See Section 12 for additional Ecological Information.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open
--------------------------------	--



flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Petroleum distillates 68476-85-7	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m ³	
Residual oils (petroleum), solvent refined 64742-01-4	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral		
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust	
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ Mo inhalable particulate matter TWA: 3 mg/m ³ Mo respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ Mo	IDLH: 5000 mg/m ³ Mo	
Chemical Name	Alberta	British Columbia	Ontario TWAEV	Quebec
Petroleum distillates 68476-85-7	TWA: 1000 ppm STEL: 1500 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 3 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves. Nitrile rubber. Rubber gloves. Neoprene gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Aerosol
Appearance Black
Odor Petroleum
Color Black
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	None	None known
Boiling point / boiling range	> 371 °C / 700 °F	None known
Flash Point	232 °C / 450 °F	Cleveland Open Cup (COC)
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.06	
Water Solubility	Insoluble	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	No data available	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information



Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	<70%
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
-----------------	--

Numerical measures of toxicity

Acute Toxicity

Unknown acute toxicity No information available

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	Inhalation LC50
Solvent naphtha (petroleum), medium aliphatic	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h

Residual oils (petroleum), solvent refined	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Molybdenum (IV) sulfide			> 2820 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity Legend	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Marine Pollutant	This product contains a chemical which is listed as a marine pollutant according to DOT
Ecotoxicity	The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), medium aliphatic	96h EC50: = 450 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 800 mg/L (Pimephales promelas)	-	48h EC50: > 100 mg/L
Residual oils (petroleum), solvent refined	-	96h LC50: > 5000 mg/L (Oncorhynchus mykiss)	-	48h EC50: > 1000 mg/L

Persistence and Degradability	No information available.
--------------------------------------	---------------------------

Bioaccumulation

Chemical Name	Log Pow
Petroleum distillates	2.8

Mobility	No information available.
-----------------	---------------------------

Other adverse effects	No information available.
------------------------------	---------------------------

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
--	--

Contaminated packaging Do not reuse empty containers.
 US EPA Waste Number D001

California Hazardous Waste Codes 331

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT
 Description UN1950, AEROSOLS, 2.1 (SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC)
 Emergency Response Guide Number 126

TDG

Proper Shipping Name AEROSOLS
 Description UN1950, AEROSOLS, 2.1

MEX

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Description UN1950, AEROSOLS, 2.1

ICAO

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Description UN1950, AEROSOLS, 2.1

IATA

UN Number UN1950
 Proper Shipping Name AEROSOLS, FLAMMABLE
 Hazard Class 2.1
 Packing Group N/A
 ERG Code 10L
 Description UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG

UN Number UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Packing Group N/A
 EmS-No. F-D, S-U
 Description UN1950, AEROSOLS, 2.1

RID

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Packing Group N/A
 Classification code 5F
 Description UN1950, AEROSOLS, 2.1



ADR

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Packing Group	N/A
Classification code	5F
Tunnel restriction code	(D)
Description	UN1950, AEROSOLS, 2.1, (D)

ADN

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, AEROSOLS, 2.1
Hazard Labels	2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture**International Regulations**

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Complies.
DSL/NDSL	Not determined.
EINECS/ELINCS	Complies.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Acute Health Hazard

No



Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Petroleum distillates 68476-85-7	X	X	X	X	
Residual oils (petroleum), solvent refined 64742-01-4					X
Graphite 7782-42-5	X	X	X		
Molybdenum (IV) sulfide 1317-33-5		X			

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties - Personal Protection X
HMIS	Health hazards 2 *	Flammability 4	Physical hazards 0	
	<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>		

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 16-Jul-2018

Revision Date 21-Feb-2019

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

