#### DRILLING COMPOUND

# **BESTOLIFE® GGT-RSC-HT**



5 Gallon Metal Pail

# **PRODUCT CHARACTERISTICS**

Color:	Black		
Penetration: (ASTM D217)	300-320		
NLGI Grade:	1		
Weight/Gallon:	10.7 pounds/gallon		
Thickener:	Lithium Complex		
Fluid Type:	Petroleum		
Dropping Point: (ASTM D2265)	≥500°F (≥260°C)		
Flash Point:	≥392°F (≥200°C)		
Brushable To:	shable To: 15°F (-9°C)		
Service Rating:	600°F (316°C)		
Friction Factor:	1.0*		
Shelf Life: (Unopened container)	4 years		
<b>Contains:</b> Synthetic and amorphous graphite and other nonmetallic additives			

<sup>\*</sup>NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmosphere.

# **DESCRIPTION**

BESTOLIFE® GGT-RSC-HT is an economical non metallic thread compound for rotary-shouldered connections. Recommended for medium to heavy duty drilling, the compound applies easily in a range of temperatures and conditions. GGT-RSC-HT is resistant to washout and will not harden or bleed excessively in storage. NSF H2 registered.\*\*

## **APPLICATIONS**

Non metallic, non conductive compound for rotaryshouldered connections.

## **TECHNICAL DATA**

BESTOLIFE® GGT-RSC-HT contains a high percentage of amorphous and synthetic graphite, as well as other inert solids, in a high-temperature base grease formulated with antiwear and oxidation inhibitors. In addition to the galling and seizing protection provided by the solids, GGT-RSC-HT also contains a soluble extreme pressure package that is surface active (adheres to metal surfaces) and helps to provide the load-carrying capability required by the high-bearing stresses present in rotary-shouldered connections. It is recommended for medium to heavy duty drilling.

## **PACKAGING**

PRODUCT	CONTAINER	CONTAINER
NUMBER	SIZE	WEIGHT
652251	5 gallon	

Note: All package sizes are not listed. Call your sales representative for a complete listing.

Rev. 022421



<sup>\*\*</sup>NSF Registration No. 141561 Category Code: H2