

DRILLING COMPOUND

MR. B



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Black
Penetration: (ASTM D217)	290-310
NLGI Grade:	1.5
Weight/Gallon:	12.7pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Service Rating:	500°F (260°C)
Friction Factor:	1.0* / 1.1**
Shelf Life: (Unopened container)	4 years
Contains:	Lead, graphite and other nonmetallic additives

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

**The proper field torque for all API casing and tubing connections should be determined by following the procedures outlined in API RP 5C1: Recommended Practice for Care and Use of Casing and Tubing.

DESCRIPTION

BESTOLIFE® Mr. B combines finely powdered metallic lead with non metallic additives to cushion joints and enhance high temperature applications. For use on drill pipe, casing, and pipeline connections of every type.

APPLICATIONS

Economical tool joint and drill pipe compound.

TECHNICAL DATA

Mr. B is a junior version of BESTOLIFE® No. 270®, containing finely powdered metallic lead in a high quality lubricating base grease formulated with H₂S and oxidation inhibitors. Special non metallic additives cushion joints and enhance high temperature properties. Provides economical protection for drill pipe, and pipeline connections of every type (except oxygen). Like BESTOLIFE® No. 270®, Mr. B is not attacked by H₂S or drilling fluids.

NOTES

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
610010	1 gallon	10 pounds plastic
610020	2 gallon	20 pounds plastic
610030	3 1/2 gallon	30 pounds plastic
610050	5 gallon	50 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

