

## DRILLING COMPOUND

# WHITE COLLAR PREMIUM



5 Gallon Plastic Pail

## PRODUCT CHARACTERISTICS

<b>Color:</b>	Light Gray
<b>Penetration:</b> (ASTM D217)	265-295
<b>NLGI Grade:</b>	2
<b>Weight/Gallon:</b>	11.4 pounds/gallon
<b>Thickener:</b>	Lithium
<b>Fluid Type:</b>	Petroleum
<b>Dropping Point:</b> (ASTM D2265)	≥350°F (≥177°C)
<b>Flash Point:</b>	≥392°F (≥200°C)
<b>Brushable To:</b>	10°F (-12°C)
<b>Service Rating:</b>	500°F (260°C)
<b>Friction Factor:</b>	1.0*
<b>Shelf Life:</b> (Unopened container)	4 years
<b>Contains:</b>	Zinc oxide, PTFE and other nonmetallic additives

\*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

## DESCRIPTION

BESTOLIFE® White Collar Premium is a versatile, effective, and premium drill collar compound that combines zinc oxide and PTFE to enhance sealing and galling resistance for both new and worn connections. White Collar Premium contains no lead and resists extreme pressure and wear.

## APPLICATIONS

Zinc/PTFE compound for drill collars.

## TECHNICAL DATA

White Collar Premium is an effective, premium drill collar compound that can be used in a wide range of drilling conditions. The combination of zinc oxide and a high percentage of PTFE provides both enhanced sealing and galling resistance in a compound that can be used on both new and worn connections. White Collar Premium includes a high level of extreme pressure and anti-wear additives that will help to reduce collar wear and damage that results in expensive re-works. White Collar Premium contains a high-quality lubricating base grease formulated with H<sub>2</sub>S and oxidation inhibitors.

## PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
626500	5 gallon	50 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

